



HVS
HOLLAND VISION SYSTEMS



(616) 494-9974



hollandvisionsystems.com



11301 James Street Holland, MI 49424

FlexCam Monitor H7W

Specs:

Camera:

Image Sensor	1/2.9 Color DSP
Wireless Module	Built-in 2.4G digital wireless transmitter
Transmit Power	18dBm
Resolution	1080P
Effective Pixels	1920(H) x 1080(V)
Infrared Distance	5M
Shell Material	Aluminum Alloy
Waterproof Level	IP69K
Working Voltage	DC5V (Battery Powered)
Cell Type	Lithium polymer battery
Battery Capacity	8000mAh/3.7v/29.6Wh
Interface Input	Type-C waterproof interface (with QC2.0 fast charge protocol) 12V//1.5A
Power Display	Fast charge indicator and 25%-50%-75%-100% battery indicator at camera front panel
Battery Switch	Touch switch
Installation	Mounting with built-in silicone-clad magnetic base
Seismic Rating	5G (According to standard of GB-T2423056-2006)
Dimensions	138(W) x 80(H) x 70(D) mm (without antenna)

Monitor:

Wireless Receiver	Built-in 2.4 wireless receiver
Picture Mode	1/2/3/4 screen mode
Working Frequency	2400-2483.5MHZ
Color LCD Display	7-inch IPS screen
Receiving Distance	200m
Automatic Frequency Hopping	80
Resolution	1024(H) x 600(V)dot
Color System	PAL/NTSC (AUTO)
Brightness (cd/m2)	600
Anti-vibration Grade	5G (GB-T2423056-2006 standard)
Operating Temperature	-20°C to 70°C
Storage Temperature	-30°C to 80°C
Load Dump	ISO16750-2 standard (24V system Us=174V, Ri=4, td=350ms)
Operating Voltage	DC8-32V
Dimensions	(L x W x T) (220 x 150 x 84mm)



The FlexCam Monitor is a **versatile camera system**. The **magnetically mounted** camera can be moved for the desired view.

- Magnetic mount camera (**portable**)
- 1080p resolution
- Useful for many applications, farming, material handling, rentals
- **Battery powered**



Scan the QR Code
to Contact Us!



@hollandvisionsystems

Holland Vision Systems, Inc. 11301 James Street Holland, MI 49424 USA
sales@hollandvisionsystems.com www.hollandvisionsystems.com (616) 494-9974

HVS9965B