

Recording System SDDVR2-TH

Capture Accidents | Document Product Condition and Damage

A comprehensive recording system equipped with **weatherproof cameras**, optional monitor and DVR, designed to *provide evidence of pallet condition, damage accountability, operator checklist adherence, and safety incident documentation.*

Specs:

Camera:






Camera Sensor	1/3" CMOS AR0130, 960p AHD
Lens	2.1mm Standard, Other Options
Shock & Vibration	10G
S/N Ratio	50dB Min. (AGC off)
Min. Illumination	0.0 Lux (IR LED Optional)
Housing	Cast Aluminum
Color	Black
Power Supply	12V - 24VDC, 0.3A (Voltage Converters are Optional)
Operating Temp.	-13°F - 176° F (-25°C - 80°C)
Dust and Moisture Resistance	IP67
Dimensions	2.4 x 2.2 in. (60 x 55mm)
Mounting	Vertical or Horizontal Surfaces. Magnetic Mounting Kit Optional

Recorder:

Max Resolution	D1 (704 x 480); PAL (720 x 576); 960p AHD (1280 x 960)
Shock & Vibration	10G
Signal Type	960P AHD (1.23MP) Maximum
Housing	Cast Aluminum
Camera Capacity	4
Storage Capacity	2 x SDHC/SDXC, 128GB Max. Each (256GB Total)
Recording Rate	1.8 GB/Hr. Approx. (142 hours/256GB One Camera Best Quality)
Color	Black
Power Supply	8 - 32VDC (Voltage Converter Available), 10W
Operating Temp	-22°F - 140°F (-30°C - 60°C)
Dust and Moisture Resistance	Not waterproof
Dimensions	5.5 x 1.6 x 5.5 in. (140 x 42 x 142mm)
Network	No



Features:

-  Designed for frequent on/off cycles with no data loss.
-  **Locking door** to prevent unauthorized access to media.
-  **Easy playback and offloading of data** with standard SD card - no data loss.
-  Supports up to four cameras.
-  One year warranty.

