

Heavy-Duty Camera System MF74Q-E

Metal Cased | Durable | Works in Freezing & Hot Temperatures

The MF74Q-E offers a **robust and weatherproof** camera system with a sealed 7" LCD monitor, touch-panel controls, a stainless steel turret-style camera, and versatile configuration options.

Specs:

Camera:

Sensor	1/3" Interline Transfer CCD
Picture Elements	NTSC; 410,000 pixels
Lens	2.9mm F2.0, 90 Degree FOV (Lens Options Available)
Shock & Vibration	10G
Resolution	520 TVL
S/N Ratio	44dB Min. (AGC off)
Min. Illumination	0.1 Lux
Housing	Stainless Steel; Nylon Bracket
Color	Black
Power Supply	12VDC, 2.2W
Operating Temp	-40F - 180F (-40 - 80C)
Weather Resistant	Yes, IP69K
Dimensions	3.2 x 2.7 x 2.5 in. (81 x 67 x 62 mm)
Video Cable	Cabled and Wireless Systems Available

Monitor:

Technology	TFT Digital Active Matrix LCD
Display Size	7" (17.8 cm) Diagonal
Housing	Aluminum, Black Finish
Signal Format	NTSC
Number of Pixels	800 (W) x 480 (H)
Shock & Vibration	5G
Brightness/Cont.	450 nits; 300:1
Video Connections	4/Split Screen Layouts
Power	Voltage Options Available, 16W
Temperature	-40°F - 158°F (-40°C - 70°C)
Weatherproof	Yes, IP69K
Dimensions	7.7 x 4.9 x 1.3 in. (194 x 124 x 32 mm)
Weight	1.8 lb. (0.8 kg)
Controls	Power, Menu, Source, +/-, OSD

Features:

-  Operate in arctic-cold to desert temperatures.
-  LED backlighting technology for *brighter image*.
-  Monitor can display an overlaid line on the screen that makes aiming the forks and judging mast tilt quicker.
-  Sony chipsets deliver 550 TV Lines resolution (37% higher than standard models).
-  One year warranty.

